

EN



Declaration of performance

DoP F200V2-F205V2-CPR-230325UKCA

PRODUCT

Product Type:	Roomheaters fired by solid fuel
Type, batch or serial number:	Jøtul F 200 V2, Jøtul F 205 V2
Intended use:	Roomheater burning solid fuel without water supply
Fuel	Wood logs

MANUFACTURER

Name:	Jøtul AS
Address:	Postboks 1411 1602 Fredrikstad, Norway
Telephone:	+47 69 35 90 00
Email:	post@jotul.no

CHECKS

According to AVCP:	System 3
Notified body:	Danish Technological Institute / KIWA
NB-No:	1235 / 0558
Test report no:	300-ELAB-2739-EN / 61675-9
Harmonized norm:	BS EN 13240:2003:AC:2006/A2:2004:AC:2007

SAFETY

Safety distance to combustible materials	Minimum distances [in mm] - (F 205 V2) Rear = 125 Sides = 400 (425) Corner = 225 (250) Front = 750 Floor = 0 Ceiling = 750 Also see the installation instructions
Fire safety	Pass
Reaction to fire	A1
Risk of burning fuel falling out	Pass
Surface temperature	Pass
Electrical safety	-
Release of dangerous substance	x
Cleanability	Pass
Maximum water operating pressure	-
Mechanical resistance (to carry a chimney/flue)	x

PERFORMANCE AND EMISSION

Essential characteristics	Performance
Emission of combustion products	Pass
CO	[0,0787 %], 984 mg/Nm ³
NOx	99 mg/Nm ³
OGC	56 mg/Nm ³
PM	14 mg/Nm ³
Flue gas temperature at the measuring section at nominal heat output [in °C]	269
Flue gas outlet temperature at nominal heat output [in °C]	323
Thermal output	Pass
Nominal heat output	5 kW
Nominal space heat output	5 kW
Nominal water heat output	-
Energy efficiency	η [82%]
Durability	x

Declaration:

The performance of the product is in conformity with the declared performance.

This declaration of performance is issued under the sole responsibility of the manufacturer.

Construction Products Regulation 2011 (retained EU Law EUR 305/2011) as amended.

Signed on behalf of the manufacturer:

Espen Auensen

R&D Manager

(Name and function)

Fredrikstad, March 2025



(Signature)