

Declaration of performance

DoP F400ECO-CPR-281022

PRODUCT

Product Type:	Roomheaters fired by solid fuel
Type, batch or serial number:	Jøtul F 400 ECO, Jøtul F 400 ECO SE
Intended use:	Roomheater burning solid fuel without water supply
Fuel	Wood logs

MANUFACTURER

Name:	Jøtul AS
Adress:	Postboks 1411 1602 Fredrikstad, Norway
Telephone:	+47 69 35 90 00
Email:	post@jotul.no

CHECKS

According to AVCP:	System 3
Notified body:	Danish Tecnological Institute / KIWA
NB-No:	1235 / 0558
Test report no:	300-ELAB-2530-EN / 61675-5
Harmonized norm:	BS EN 13240:2003:AC:2006/A2:2004:AC:2007

SAFETY

Safety distance to combustible materials	Minimum distances [in mm]
	Rear = 350
	Sides = 350
	Front = 1100
	Floor = 0
	Ceiling = 750
	Also see the installation instructions
Fire safety	Pass
Reaction to fire	A1
Risk of burning fuel falling out	Pass
Surface temperature	Pass
Electrical safety	-
Release of dangerous substance	х
Cleanability	Pass
Maximum water operating pressure	-
Mechanical resistance (to carry a chimney/flue)	х

PERFORMANCE AND EMISSION

Essential characteristics	Performance
Emission of combustion products	Pass
со	[0,0583 %], 729 mg/Nm ³
NOx	84 mg/Nm3
OGC	42 mg/Nm3
PM	6 mg/Nm3
Flue gas temperature at the measuring section at nominal	
heat output [in °C]	247
Flue gas outlet temperature at nominal heat output [in °C]	296
Thermal output	Pass
Nominal heat output	7 kW
Nominal space heat output	7 kW
Nominal water heat output	-
Energy efficiency	η [83%]
Durability	х

Declaration:

The performance of the product is in conformity with the declared performance.

This declaration of performance is issued under the sole responsibility of the manufacturer.

Construction Products Regulation 2011 (retained EU Law EUR 305/2011) as amended.

Signed on behalf of the manufacturer:

Sigrid B. Slang

Lab Engineer

(Name and function)

Fredrikstad, October 2022

Signature) Slang.