

Declaration of Performance (DoP)

No. F 400-CPR-130829	
Product Type:	Roomheaters fired by solid fuel
Type, batch or serial number:	Jøtul F 400
Intended use of the product:	Roomheater burning solid fuel without water supply
Name and Address of the manufacturer:	Jøtul AS
	Postboks 1411, 1602 Fredrikstad, Norway
	Tel.: +47 69 35 90 00
	E-mail: post@jotul.no
AVCP:	System 3
System(s) of assessment and verification of constancy op	
performance (AVCP) of the construction product as set out in	
CPR, Annex V	Division by the second state of the Head CONTEST AND the
Notified body:	Rhein-Ruhr Feuerstätten Prüfstelle / SINTEF NBL as
NB-No:	1625 / 1084
Test report no:	RRF-40 01 01 / SINTEF 102042.81
Declared performance:	
Harmonized technical specification	EN 13240:2001/A2:2004/AC:2007
Essential characteristics	Performance
Fire safety	
Reaction to fire	A1
Distance to combustible materials	Minimum distances, in mm
Distance to compastible materials	
	Rear = 700
	Sides = 570
	Corner = 570
	Front = 1000
	See also the installation instructions
Risk of burning fuel falling out	No
Emission of combustion products	CO [0,12 %]
	NOx [144 mg/m3]
	OGC [98 mgC/m3]
	PM [66 mg/m3]
Surface temperature	Pass
Electrical safety	- Page
Cleanability Maximum water operating pressure	Pass
Maximum water operating pressure	- T[220°C]
Flue gas temperature at nominal heat output Mechanical resistance (to carry a chimney/flue)	T [230°C] NPD
Thermal output	INFU
Normal heat output	7 kW
Room heating output	- kW
Water heating output	- kW
Energy efficiency	η [84%]

|--|

The performance of the product in conformity with the declared performance.

This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed on behalf of the manufacturer:

Tom J. Berglind

R&D Manager

(Name and function)

Fredrikstad, August 29th, 2013

(Place and date of issue)

(Sianature)